

# Just Perfect.

**Endless Productivity Made Swift** 



The all-new 36" **imagePROGRAF TM-5355** and **TM-5350** large format printers empower every print delivery with enhanced scanning operability and printer processing power, delivering high quality CAD drawings, photos and posters. Redefine your workplace productivity with a seamless, swift and reliable print partner.

# **Printing Productivity Driven By Swift Efficiency**

Push printing productivity forward with the all-new 36" **imagePROGRAF TM-5355** and **TM-5350** large format printers, which offer powerful scanning and printing capabilities, alongside versatile multi-application printing for engineering firms to drive greater business efficiency overall.

### **Swift and Productive**

The new **L-COA PRO II high-speed imaging processing chip** facilitates swift startups from sleep mode as well as continuous printing by providing improved data processing power, improving overall printing efficiency.



L-COA PRO II

**Print Speed** 

**Conventional printers** 

TM-5350/TM-5355

More than 20% faster\*

\*Based on Canon internal testing using plain paper with continuous printing of A1 page per min

# **Enhancing Prints with Vivid Red**

The **brand new magenta ink** offers a more vivid red on CAD drawings, posters and photos that help to improve clarity and details.

# **Borderless Printing Made Easy**

**Borderless poster printing** on any size of roll paper is possible with the TM-5350 and TM-5355.




# **Making User Operation Easy**

The new design of the printer features a **flat top space** for roll paper replacement or for placing output prints.



The **automatic paper type detection** allows for easy viewing of paper media details and the balance of roll paper within the printer.



## **Smoother, Easier Workflows**

Streamline how you manage workflows with convenient and intuitive software applications.

#### **Direct Print Plus**

The Direct Print Plus feature allows you to **print PDF or JPEG files in batches** with custom templates with minimal effort.



#### **Free Layout Plus**

Documents can be resized easily with Free Layout Plus, which allows files to be dragged and dropped into the software for **easy document** resizing to specific paper layouts.



#### **Accounting Manager**

Monitor and **keep track of print usage** with ease using the
Accounting Manager application.



#### **PosterArtist**

#### **Design vibrant posters**

for your needs with minimal effort using the PosterArtist application.



Check it out at <a href="https://posterartist.canon">https://posterartist.canon</a>







# **Scanning with Efficiency**

The Lm36 scanner can be used with the TM-5350, which comes with improved scanning functions that boost productivity and operability through a maximum paper thickness of 0.8mm alongside featuring brand new transparent guides.



TM-5350 MFP Lm36

The **TM-5355** is able to utilise the **Z36 scanner** which offers easier troubleshooting by providing a **web manual link** when a printer error occurs. It also features a roll removal button, alongside effortless information retrieval of the **amount of roll paper remaining** in the printer.



TM-5355 MFP Z36

#### **SPECIFICATIONS**

Printer Type		TM-5350	TM-5355	PRINT SPEED	¹⁴ (A1 SIZE)	TM-5350	TM-5
		5-Colour, 36"			CAD Drawing		
Number of Nozzles		15,360 nozzles (MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each)		Plain Paper	(A1 Landscape, Fast Q5 mode)	17 :	sec
Max. Print Resolution		2,400 x 1,200 dpi			CAD Drawing		
Nozzle Pitch	.e1		dpi x 2		(A0 Portrait, Fast Q5 mode)	32	sec
Line Accuracy	Sales Ink		or less MBK, BK, C, M, Y)	Heavyweight	Poster		
Ink Bottle	Bundle			Coated Paper	(A0 Portrait, Standard mode)	2 min	33 sec
Size	Starter Ink	130 ml (MBK) / 9	0 ml (BK, C, M, Y)	MEDIA HANDI			
Ink Type		Pigmo	ent Ink		Roll Paper		
		SG Raster (Swift Graphic Raster)		Media Width Cut Sheet		203.2 ~ 917 mm	
Print Languages		HP-GL/2, HP RTL JPEG (Ver. JFIF1.02)		Media	Roll Paper/		
		CAL	S G4*2	Thickness	Cut Sheet		
Print Solutions and Applications		PDF  Printer Driver (Win/Mac Versions), Direct Print Plus, Free Layout Plus, PosterArtist Windows/Web & Lite, Wi-Fi Connection Assistant, PIXMA Cloud Link, Apple AirPrint (Mobile), Canon PRINT Inkjet/ SELPHY (Mobile), Canon Print System (Mobile), uniFlow Server		Printable Roll Paper Media Length Cut Sheet		203.2 mm ~ 18 m <sup>*5</sup> 279.4 ~ 1,600 mm	
				Media Core Size		2/9.4 ~ 1,000 mm	
				Outside Diameter Roll Paper		150 mm or less	
		· · ·			Roll Paper	1 Roll, Top Loa	
Management	Solutions	Media Configuration Tool (includes Color Customisation Tool), Accounting Manager, Device Management Console, Quick Utility Toolbox		Media Feed	Cut Sheet	Front Load, Front Output	
				Delivery Direc	tion	Face-up, Front Side	
	USB B Port		oit/sec), Hi-Speed (480 Mbit/sec), Series B (4 pins)		Recommended Area	20 mm 2	mm 2 mm
		Duk Hallslei, C	USB Memory (Direct Print)		(Roll Paper)	20 mm, 3 mm, 3 mm	
	USB A Port	-	Supported file format: JPEG/PDF		Recommended	00 00	2
	Network		3 10base-T		Area (Cut Sheet)	20 mm, 20 mm, 3 mm	
		IEEE 802.3u 100base-TX IEEE 802.3ab 1000base-T IEEE 802.3x Full Duplex		Margins (Top, Bottom, Side)	Printable Area	3 mm, 3 mm, 3 mm	
Interface (Built-in)					(Roll Paper)	3 11111, 3 11111, 3 11111	
(Built-III)	Wireless LAN		/IP (IPv4/IPv6), FTP	,	Printable Area (Roll Paper		
		IEEE802.11 b/g/n WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES) WPA3-SAE (AES) WPA-EAP (AES)' <sup>3</sup>			Borderless	0 r	nm
					Print)		
					Printable Area (Cut Sheet)	3 mm, 20 mm, 3 mm	
			AP(AES)*3	DIMENSIONS (W x D x H) & WE		EIGHT' <sup>6</sup>	
		2 GB	AP(AES)*3 128 GB (Physical Memory 2 GB)		Printer (Main		
Memory Hard Disk		No Hard Disk	500 GB (Encrpyted) Hard Disk	Packaged	unit + Stand + Basket +	1,462 x 1,12	
Display		LCD (4.3 inch / 1	0.9 cm TFT color)	Dimensions	Pallet)	Weight	: 113 kg
	Please visit				(SD-35)	1005 740 400 40	
os	https://asia. canon to confirm	Windows	Macintoch		Printer	1,285 x 748 x 439 mm (Ope Weight: 49.5 kg (Exclud	
Compatibility		Windows, Macintosh		Printer &	Printer with		
	the latest drivers.			Weight	Stand +	1,285 x 885 x 1,060 mm (Operation p 1,285 x 756 x 1,060 mm (Operation	
SCANNER					Basket (SD-35)	Weight: 63.8kg (Exclud	ing print head and
Scanner Mode	el	Lm36	Z36 6"			1,238 x 253 x 131 mm	1,056 x 251
Scan Width		Up to 600 dpi	Up to 1200 dpi	Scanner & We	ight	Weight: 6.56 kg	Weight: System Controlle
Ontical Becol							
Optical Resolu	ution (DPI)			POWER & OPI	ERATING REQUI		Gyotom Controllo
Optical Resolution	ution (DPI)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG	POWER & OPI	ERATING REQUIF	REMENTS	/ (50 - 60 Hz)
Scan Format	. , ,	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB,	Power Supply		REMENTS	
•	. , ,	TIFF, TIFF G4, PDF, PDF/A, JPEG	TIFF, TIFF 64, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)	Power Supply Power Consumption	(Printer)	AC 100-240 \	/ (50 - 60 Hz)
Scan Format	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB,	Power Supply	(Printer) Operation	AC 100-240 \	/ (50 - 60 Hz) < 69
Scan Format Scan Destinat	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG Scan to PC, USB ScanAPP Colour	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks	Power Supply Power Consumption (Printer) Recommended	(Printer) Operation Sleep Mode Power OFF Temperature	AC 100-240 V < 65 W < 1 < 0	/ (50 - 60 Hz)
Scan Format Scan Destinat	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour Draft (300/300 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)	Power Supply Power Consumption (Printer)	(Printer) Operation Sleep Mode Power OFF Temperature Humidity	AC 100-240 \ < 65 W < 1 < 0.0 15 - 3 10 - 80% RH (no c	/ (50 - 60 Hz)
Scan Format Scan Destinat	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec	Power Supply Power Consumption (Printer) Recommended	(Printer)  Operation  Sleep Mode  Power OFF  Temperature  Humidity  Power'7	AC 100-240 \ < 65 W < 1. < 0. < 10 - 80% RH (no company)  Approx.	/ (50 - 60 Hz)  < 69 6 W 1 W 30 °C lew condensation) 6.2 Bels
Scan Format Scan Destinat	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)	Power Supply Power Consumption (Printer) Recommended Environment Acoustics	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' <sup>7</sup> Pressure <sup>7</sup>	AC 100-240 \ < 65 W < 1 < 0.0 15 - 3 10 - 80% RH (no c	/ (50 - 60 Hz)  < 69 6 W 1 W 30 °C lew condensation) 6.2 Bels
Scan Format Scan Destinat	tions	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' <sup>7</sup> Pressure <sup>7</sup>	AC 100-240 \ < 65 W  < 1 < 0.0  15  10 - 80% RH (no c  Approx.  Approx. 41 dB(A), Sta	/ (50 - 60 Hz)  < 69 6 W 1 W 30 °C lew condensation) 6.2 Bels
Scan Format Scan Destinat Scanner Softv	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' CESSORIES	AC 100-240 \ < 65 W < 1. < 0.0 10 - 80% RH (no c.) Approx. 41 dB(A), Sta	/ (50 - 60 Hz)  < 69 6 W  .11 W .30 °C lew condensation) 6.2 Bels ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mp per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' <sup>7</sup> Pressure' <sup>7</sup> CCESSORIES	AC 100-240 \ < 65 W < 1. < 0.0 10 - 80% RH (no c.) Approx. 41 dB(A), Sta	/ (50 - 60 Hz)  < 69 6 W 11 W 30 °C 30 °C 6.2 Bels ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec  Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec	Power Supply Power Consumption (Printer)  Recommended Environment  Acoustics  OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power'7 Pressure'7 CCESSORIES er + Basket	AC 100-240 \ < 65 W < 1.	/ (50 - 60 Hz)  < 69 6 W .1 W .30 °C lew condensation) 6.2 Bels ndby 35 dB(A) or le - 2-35
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CCESSORIES  er + Basket Interface	AC 100-240 \ < 65 W < 1.	/ (50 - 60 Hz)  < 69 6 W 11 W 30 °C 30 °C 6.2 Bels ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec  Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec	Power Supply Power Consumption (Printer)  Recommended Environment  Acoustics  OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CCESSORIES  er + Basket Interface	AC 100-240 \ < 65 W < 1. < 0.0 10 - 80% RH (no c. Approx. 41 dB(A), Sta	/ (50 - 60 Hz)  < 69 6 W 10 W 30 °C 6.2 Bels 10 Bels 1
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 15 ips /38.1 mm per sec Best (600/600 dpi): 15 ips /38.1 mm per sec Colour	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec  Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CCESSORIES  er + Basket Interface	AC 100-240 \ < 65 W < 1.	/ (50 - 60 Hz)  < 69 6 W .1 W .30 °C lew condensation) 6.2 Bels andby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 3.1 ips / 330.2 mm per sec 300 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CCESSORIES  er + Basket Interface	*** AC 100-240 \( < 65 \)	/ (50 - 60 Hz)  < 69 6 W  11 W 30 °C lew condensation) 6.2 Bels ndby 35 dB(A) or le ml) / PFI-8321 (300 ml) / P
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips /38.1 mm per sec  Colour  Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi):	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec Monochrome / Greyscale (8 bit) 200 dpi: 13 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure' + Basket Interface	REMENTS  AC 100-240 \  < 65 W  < 1.  < 0.  10 - 80% RH (no c.  Approx.  Approx. 41 dB(A), Sta  RH2  RA  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF	/ (50 - 60 Hz)
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	tions ware eed:	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 15 ips / 33.1 mm per sec Colour  Draft (200 dpi): 1 ips / 25.4 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per s	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance (	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure' + Basket Interface ES	REMENTS  AC 100-240 \  < 65 W  < 1.  < 0.  10 - 80% RH (no c.  Approx.  Approx. 41 dB(A), Sta  RH2  RA  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF  CT  MC	/ (50 - 60 Hz)  < 69 6 W  11 W 30 °C lew condensation) 6.2 Bels ndby 35 dB(A) or le ml) / PFI-8321 (300 ml) / P
Scan Format Scan Destinat Scanner Softv Max. Copy Sp (inch/sec) or	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 18.38 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader Is for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CESSORIES  er + Basket Interface ES  Cartridge re subject to change	### AC 100-240 \	/ (50 - 60 Hz)  6 W 1.1 W 30 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softv Max. Copy Sp (inch/sec) or	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 15 ips /38.1 mm per sec  Colour  Draft (200 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.8 ips / 18.38 mm per sec Monochrome	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 3 ips / 76.2 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 300 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader It for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of Specifications as " User adjustmer	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CESSORIES  er + Basket Interface ES  Cartridge re subject to change	AC 100-240 \\ < 65 W  < 1. < 0.  15 - C  10 - 80% RH (no c  Approx. 41 dB(A), Sta  RH2  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF  CT  MC  ge without notice. environment and media must match the	/ (50 - 60 Hz)  6 W 1.1 W 30 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softw Max. Copy Sp	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 18.38 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader Is for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance ( Specifications as " User adjustmer Paper required 2" USB Thumb dri	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure' Pressure'  CESSORIES  er + Basket Interface ES  Cartridge re subject to changes required. Printing Plain paper and cover printing is not sure to support to the content of t	AC 100-240 \  < 65 W  < 1.  < 0.  10 - 80% RH (no c.  Approx.  Approx. 41 dB(A), Sta  RH2  RA  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF  CT  MC  ge without notice. environment and media must match the ated paper only. pported.	/ (50 - 60 Hz)  6 W 1.1 W 30 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le
Scan Format Scan Destinat Scanner Softv Max. Copy Sp (inch/sec) or	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 0.5 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.3 ips / 8.38 mm per sec Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 0.3 ips / 78.2 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 600 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 000 dpi: 3 ips / 76.2 mm per sec 300 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 30.2 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader Is for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of Specifications as " User adjustmer Paper required 2 USB Thumb dri 3 IEEE802.1X (EA	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' Pressure'  CESSORIES  er + Basket Interface ES  Cartridge re subject to changes required. Printing the Plain paper and cover printing is not supported by the Palance of the Palance o	AC 100-240 \  < 65 W  < 1.  < 0.  10 - 80% RH (no c.  Approx. 41 dB(A), Sta  Approx. 41 dB(A), Sta  RH2  RA  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF  CT  MC  ge without notice. environment and media must match the ated paper only. pported.  EAP) supported.	/ (50 - 60 Hz)  6 W 10 W 10 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le  2-35 02  ml) / PFI-8321 (300 n PFI-8120 (130 ml) / P -06 -08 2-31  sse used for the adjusting the statement of the
Scan Format Scan Destinat Scanner Softv Max. Copy Sp (inch/sec) or	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome  Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 35.4 mm per sec Standard (300 dpi): 1.5 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.33 ips / 8.38 mm per sec Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.5 ips / 38.1 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox) SmartWorks (includes system controller)  Colour (24 bit) 200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 4.3 ips / 109.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec	Power Supply Power Consumption (Printer)  Recommended Environment  Acoustics  OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance of Specifications as " User adjustmer Paper required 2 USB Thumb dri 3 IEEE802.IX (EA	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' **CESSORIES  er + Basket Interface **ES  Cartridge re subject to change its required. Printing is not support of the printing is not suppo	AC 100-240 \  < 65 W  < 1.  < 0.  10 - 80% RH (no c.  Approx.  Approx. 41 dB(A), Sta  RH2  RA  Magenta: PFI-8121 (130  Matte Black / Black / Cyan / Yellow:  PF  CT  MC  ge without notice. environment and media must match the ated paper only. pported.	/ (50 - 60 Hz)  6 W 10 W 10 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le  2-35 02  ml) / PFI-8321 (300 n PFI-8120 (130 ml) / P -06 -08 2-31  sse used for the adjusting the statement of the
Scan Format Scan Destinat Scanner Softv Max. Copy Sp (inch/sec) or	eed: (mm/sec)	TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG  Scan to PC, USB  ScanAPP  Colour  Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 0.5 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec  Monochrome Draft (300/300 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.3 ips / 8.38 mm per sec Monochrome Draft (200 dpi): 3 ips / 76.2 mm per sec Standard (300 dpi): 0.3 ips / 78.2 mm per sec	TIFF, TIFF G4, PDF, PDF/A, JPEG, DWF Multipage PDF/PDF/A, TIFF/JPEG  Scan to PC, Shared Folders, USB, FTP, Email, Cloud (Dropbox)  SmartWorks (includes system controller)  Colour (24 bit)  200 dpi: 6 ips / 152.4 mm per sec 300 dpi: 4 ips / 101.6 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 600 dpi: 3 ips / 76.2 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 2 ips / 50.8 mm per sec 600 dpi: 3 ips / 330.2 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 600 dpi: 3 ips / 50.8 mm per sec 800 dpi: 3 ips / 330.2 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec 300 dpi: 8.6 ips / 218.4 mm per sec	Power Supply Power Consumption (Printer) Recommended Environment Acoustics OPTIONAL AC Roll Unit 2/3" Roll Hold Printer Stand Card Reader I for uniFLOW CONSUMABL Ink Tank Print Head Cutter Blade Maintenance ( Specifications ai " User adjustmer Paper required 2" USB Thumb dri " USB Thumb dri " USB Thumb dri " IEEE802.1X (EA	(Printer) Operation Sleep Mode Power OFF Temperature Humidity Power' Pressure' **CESSORIES  er + Basket Interface **ES  Cartridge re subject to change its required. Printing is not support of the printing is not suppo	AC 100-240 \  < 65 W < 1. < 0. 15 - 3 10 - 80% RH (no concentration of the process of the proce	/ (50 - 60 Hz)  6 W 10 W 10 °C  lew condensation) 6.2 Bels  ndby 35 dB(A) or le  2-35 02  ml) / PFI-8321 (300 n PFI-8120 (130 ml) / P -06 -08 2-31  sse used for the adjusting the statement of the

PRINT SPEED	4 (A1 SIZE)	TM-5350	TM-5355		
	CAD Drawing (A1 Landscape,	17 :	sec		
Plain Paper	Fast Q5 mode)	17 360			
	(A0 Portrait, Fast Q5 mode)	32 sec			
Heavyweight Coated Paper	Poster (A0 Portrait, Standard mode)	2 min 33 sec			
MEDIA HANDL					
80 - di - 180 deb	Roll Paper	000.0 017			
Media Width	Cut Sheet	203.2 ~ 917 mm			
Media Thickness	Roll Paper/ Cut Sheet	0.07 ~ 0.8 mm			
Printable	Roll Paper	203.2 mm ~ 18 m <sup>15</sup>			
Media Length	Cut Sheet	279.4 ~ 1,600 mm			
Media Core Size		2 inch / 3 inch core			
Outside Diame		150 mm or less			
Media Feed	Roll Paper	1 Roll, Top Load, Front Output			
	Cut Sheet	Front Load, Front Output			
Delivery Direct		Face-up, Front Side			
	Recommended Area (Roll Paper)	20 mm, 3 mm, 3 mm			
	Recommended				
Margins	Area (Cut Sheet)	20 mm, 20 mm, 3 mm			
(Top, Bottom, Side)	Printable Area (Roll Paper)	3 mm, 3 mm, 3 mm			
	Printable Area (Roll Paper Borderless Print)	0 mm			
	Printable Area (Cut Sheet)	3 mm, 20 mm, 3 mm			
DIMENSIONS	(W x D x H) & WE	IGHT'6			
Printer (Main unit + Stand + Basket + Pallet)		1,462 x 1,122 x 801 mm Weight: 113 kg			
	(SD-35) Printer	1,285 x 748 x 439 mm (Operation panel not tilted up) Weight: 49.5 kg (Excluding print head and ink)			
Printer & Weight	Printer with Stand + Basket (SD-35)	1,285 x 885 x 1,060 mm (Operation panel not tilted up / Basket opened 1,285 x 756 x 1,060 mm (Operation panel not tilted up / Basket closed) Weight: 63.8kg (Excluding print head and ink)			
Scanner & Weight		1,238 x 253 x 131 mm Weight: 6.56 kg	1,056 x 251 x 156 mm Weight: 7.8 kg System Controller Weight: 2.5 kg		
POWER & OPE	RATING REQUIF	REMENTS			
Power Supply	(Printer)	AC 100-240 V	/ (50 - 60 Hz)		
Power	Operation	< 65 W	< 69 W		
Consumption	Sleep Mode	< 1.6 W			
(Printer)	Power OFF		< 0.1 W		
Recommended	Temperature	15 - 30 °C			
Environment	Humidity	10 - 80% RH (no dew condensation)			
Acoustics	Power*7	Approx. 6.2 Bels			
OPTIONAL CO	Pressure*7	Approx. 41 dB(A), Standby 35 dB(A) or less			
OPTIONAL AC	CESSURIES				
		- PUO OF			
2/3" Roll Holder Printer Stand + Basket		RH2-35			
Card Reader Interface		-			
for uniFLOW		RA	-02		
CONSUMABLE	ES				
Ink Tank		Magenta: PFI-8121 (130 ml) / PFI-8321 (300 ml) Matte Black / Black / Cyan / Yellow: PFI-8120 (130 ml) / PFI-8320 (300 ml)			
Print Head		PF-06			
Cutter Blade		CT-08			
Maintenance C	Cartridge	MC	C-31		
User adjustmen Paper required:	re subject to chang ts required. Printing Plain paper and co ve printing is not su	environment and media must match the ated paper only.	ose used for the adjustments.		
<sup>3</sup> IEEE802.1X (EA	P-TLS/EAP-TTLS/P		ssing, data transfer		



### SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS **CANON SINGAPORE PTE. LTD.** 1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Delighting You Always

Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

**DEALER'S STAMP** 

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.