

High performance, intuitive usability, versatile finishing

The imageRUNNER ADVANCE DX 8900 Series delivers high performance and quality black-and-white output for high volume office environments and CRDs. These intelligent systems enhance productivity with versatile finishing options while maintaining an intuitive user experience.



WORKFLOW EFFICIENCY

- An intuitive user interface with a large, responsive colour touchscreen makes carrying out tasks easy.
- Scalable support for mobile and flexible work styles can increase efficiency by allowing workers to capture or print documents and access certain cloud applications on the go.
- Advanced Personalisation enables a unique, personal experience across a fleet, creating a customized user experience tailored to meet each user's workflow needs.
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint files through a single-pass duplexing document feeder that holds up to 200 originals.
- Create professional-looking reports, booklets, newsletters, manuals, proposals, and contracts with flexible finishing options such as professional punching, folding, document insertion, and bookletmaking.

COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimizing downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralized fleet management can help simplify IT management of devices and entire fleets.

SECURITY

- Control who has access to the device with authentication by using the standard Universal Login Manager application.
- Help prevent unauthorized distribution of sensitive information with an array of standard and optional document security features.
- Help ensure information privacy and security across your entire network with IPsec, port filtering capabilities, and SSL technology.

DEVICE AND FLEET MANAGEMENT EFFICIENCY

- The ability to pre-configure devices makes installation easy and fleet management is simplified with the capability to synchronize settings across multiple devices.
- Canon's device management tools give you a centralized point of control across your entire fleet, including the ability to check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers.
- Standard Genuine Adobe PostScript and PCL support integration with enterprise applications and legacy systems to help streamline business processes.

RELIABILITY

- Canon's signature reliability and engine technologies provide reliable high quality output to meet the needs of busy departments and Central Reprographics Departments (CRDs)/In-plant Printers.

- State-of-the-art imaging technologies and toner allow for consistently striking images in rich black-and-white tones and 1,200 dpi print resolution.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished, intuitive user maintenance videos, the ability to replace toner on the fly, and automatic job re-routing (with optional solutions).

SUSTAINABILITY

- Fusing technologies, pO toner, and innovative sleep mode features help lower overall energy consumption.
- Help minimize waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, helping to achieve the results you want the first time.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimizing environmental impact.
- ENERGY STAR qualified and rated EPEAT Silver.

MACHINE SPECIFICATION

MAIN UNIT

Machine Type

A3 Monochrome Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store and Optional Fax

Processor

1.8GHz Dual Core Processor

Control Panel

Standard : 10.1" TFT LCD WSVGA Colour Touch panel
Optional : 10.4" TFT LCD SVGA Colour Upright Touch panel

Memory

Standard: 4GB(Main CPU Side:2GB Image Processing CPU Side:1GB - 1GB (Image processing only)

Hard Disk Drive

Standard*: (SSD) 256 GB

Optional : (SSD) 1TB

* A different initial HDD may be used.

Mirroring Hard Disk Drive

Optional

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T,
Optional : Wireless LAN (IEEE 802.11 b/g/n)

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host) X1,
USB 2.0 x1 (Device) X1;
Optional: Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)

Standard: 4,200 sheets

100-sheet Multi-purpose tray x1
1,500-sheet Paper Deck x 2
550-sheet Paper Cassette x 2

Maximum: 7,700 sheets (with POD Deck Lite-C1 or POD Deck Unit-E1)

Paper Output (A4, 80gsm)

250 Sheets (with Copy Tray-R2)

Maximum: 5,000 sheets (High-Volume Stack mode "ON" with Staple Finisher-W1 PRO or Booklet Finisher-W1 Pro)

Finishing Capabilities

With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold, Double Parallel-fold, Trimming

Supported Media Types

Paper Decks (Right/Left):

Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead

Paper Cassettes (Upper/Lower):

Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead, Tab*

*Requires Tab Feeding Attachment-B1.

Multi-purpose Tray:

Thin, Plain, Recycled, Color, Heavy, Tracing*, Bond, Transparency, Labels, Pre-punched, Letterhead, Tab

* Some types of tracing paper cannot be used.

Supported Media Sizes

Upper Left/Right Cassettes (1/2):

Standard size: A4, B5

Lower Cassettes (3/4):

Standard size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R
Custom size: 139.7 x 182.0 mm to 330.2 x 487.7 mm

Multi-purpose Tray:

Standard size: SRA3, A3, A4, A4R, A5* 1, A5R, A6R* 2, B4, B5, B5R

Custom Size : 100.0 x 148.0 mm to 330.2 x 487.7 mm

Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm

*1 Supported media weights: more than 64 gsm

*2 Supported media weights: more than 91 gsm

Supported Media Weights

Paper Deck (Right/Left): 52 to 220 gsm

Paper Cassette (Upper/Lower): 52 to 220 gsm

Multi-purpose tray: 52 to 256 gsm

Duplex: 52 to 220 gsm

Warm-up Time

From Power On: 60 Seconds or Less*1

From Sleep Mode: 60 Seconds or Less

Quick Start-up Mode: 4 Seconds or Less*2

*1 Time from device power-on, until copy ready(not print reservation)

*2 Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display

Dimensions (W x D x H)

Standard: 670 mm x 770 mm x 1,185 mm

(including 1-pass DADF and flat touch panel)

With optional Upright Control Panel: 1,170 x 770 x 1,252 mm

Installation Space (W x D)

Basic: 1,533 x 1,353 mm (with Multi-purpose tray/upper-right cover open + Front cover open + Copy Tray)

Fully configured: 5,068 x 1,409 mm (with POD Deck Lite-C1 + Document Insertion Unit-N1 + Multifunction Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet Finisher-W1 Pro + Booklet Trimmer-F1 + Main unit Front Cover open)

Weight

Standard : Appro x. 221 kg

With optional Upright Touch Panel : Appro x. 225 kg

Printing Specifications

Print Speed

iR-ADV DX 8905 : Up to 105 ppm (A4), Up to 54 ppm (A3),
Up to 76 ppm (A4R), Up to 105 ppm (A5R)

iR-ADV DX 8995 : Up to 95 ppm (A4), Up to 50 ppm (A3),
Up to 69 ppm (A4R), Up to 95 ppm (A5R)

iR-ADV DX 8986 : Up to 86 ppm (A4), Up to 44 ppm (A3),
Up to 63 ppm (A4R), Up to 86 ppm (A5R)

Print Resolution (dpi) 1,200 x 1,200

Page description languages

Standard : UFR II (standard),

Optional : PCL 6, Genuine Adobe PostScript Level 3

Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

Printing from mobile and cloud

AirPrint, Mopria, Google Cloud Print, Canon Print Business, and uniFLOW Online

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

OS Standard Printing

Android, Windows® 10/11, Chrome OS, macOS(11.2.2 or later), iOS (15.2 or later), iPadOS

Fonts

PS fonts: 136 Roman

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts *2

*1 Requires optional PCL INTERNATIONAL FONT SET-A1

*2 Requires optional BARCODE PRINTING KIT-D1

Printing Features

Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer.

Operating System

UFR II : Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2016/Server 2022, MAC OS X (10.13 or later)

PCL : Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022

PS : Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X(10.13 or later)

PPD : Windows®10/11, MAC OS X (10.13 or later)

As of Feb, 2023.

Copy Specifications

Copy Speed

iR-ADV DX 8905 : Up to 105 ppm (A4), Up to 54 ppm (A3),
Up to 76 ppm (A4R), Up to 105 ppm (A5R)

iR-ADV DX 8995 : Up to 95 ppm (A4), Up to 50 ppm (A3),
Up to 69 ppm (A4R), Up to 95 ppm (A5R)

iR-ADV DX 8986 : Up to 86 ppm (A4), Up to 44 ppm (A3),
Up to 63 ppm (A4R), Up to 86 ppm (A5R)

First-Copy-Out Time (A4) Approx. 2.7 seconds or less

Copy Resolution (dpi) 600 x 600

Multiple Copies Up to 9,999 copies

Copy Density Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% - 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder [2-sided to 2-sided (Automatic)]

* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80gsm)

up to 200 sheets

Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional objects

Document Feeder media weight:

1-sided scanning : 38 to 220 gsm

2-sided scanning : 38 to 220 gsm

*An acceptable weights of A6R or smaller is 50 to 220gsm.

Supported Media Sizes

Platen: max. scanning size: up to 297.0 x 431.8 mm

Document Feeder media size:

A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,

Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

Scan Speed (ipm: BW/CL; A4)

Single Pass DADF-C1:

1-sided Scanning : 135/135 (300 x 300 dpi, send),

135/80 (600 x 600 dpi, copy)

2-sided Scanning : 270/270 (300 x 300 dpi, send),

165/90 (600 x 600 dpi, copy)

Scan Resolution (dpi)

Scan for Copy : 600 x 600

Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/

IFAX), (Pull) 600 x 600

Scan for Fax : 600 x 600

Pull Scan Spec

Colour Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows® 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022

Send Specifications

Destination

E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box, Super G3 FAX(Optional), IP Fax(Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

Push : up to 600 x 600
Pull : up to 600 x 600

Communication Protocol

File : FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV
E-mail/I-Fax : SMTP, POP3

File Format

Standard : TIFF, JPEG, PDF(Limited Color, Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS(Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines 2

Modem Speed Super G3 : 33.6 kbps
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi): 400x400 (Ultra Fine),
200x400 (Super Fine),
200x200 (Fine),
200x100 (Normal)

Sending/Receiving Size

Sending : A3, A4, A4R, A5*1, A5R*1, B4, B5*2, B5R*1
Receiving : A3, A4, A4R, A5R, B4, B5, B5R
*1 Sent as A4 *2 Sent as B4 short

FAX Memory Up to 30,000 pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

Store Specifications

Mail Box Simple (Number supported)

100 User Inboxes, 1 Memory RX Inbox,
50 Confidential Fax Inboxes
30,000 Maximum Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows (Windows® 10/11) Concurrent
Connections (Max.): SMB: 64, WebDAV: 3

Advanced Box Available Disc Space

Approx. 16GB (Standard HDD)
Approx. 480GB (with option 1TB HDD)

Security Specifications

Authentication

Standard : User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

Document Security

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print™)

Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically)

Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights

Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control)
Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark)

*1 Requires uniFLOW Online / uniFLOW

Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface)

Device Security

Protecting SSD Data (SSD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Automatic Recovery, Runtime Intrusion Detection), Common Criteria Certification (HCD-PP) (pending confirmation)

Device Management and Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Environment Specifications

Operating Environment

Temperature: 10 to 30 °C
Humidity: 20 to 80 % RH (Relative Humidity)

Power Source 220-240V, 50-60Hz, 10A

Power Consumption

Maximum: 2,400W
Standby: Approx. 217 W *1
Sleep mode: Approx. 0.9 W *2

*1 Reference Value

*2 0.9W sleep mode is not available in all circumstances due to certain settings.

Consumables

Toner Cartridge : NPG-53 Black Toner
Toner Yield (Estimated Yield @6% Coverage): 70,000 pages

Software and Printer Management

Tracking and reporting

Universal Login Manager (ULM)
uniFLOW Online Express

Remote Management Tools

iW Management Console
eMaintenance
Content Delivery System

Scanning Software

Network ScanGear

Optimisation Tools

Canon Driver Configuration Tool
NetSpot Device Installer

Platform

MEAP (Multifunctional Embedded Application Platform)

Document Publishing

IW DESKTOP

Paper Supply Options

PAPER DECK UNIT-E1

Paper Capacity : 3,500 Sheets (80gsm)
Paper Type : Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead
Paper Size : A4, B5
Paper Weight : 52 to 256 gsm
Power Source : From the Main Unit

Dimensions (WxDxH) : 340 x 630 x 572 mm
(attached to the main unit)
Weight : Approx. 34 kg

POD DECK LITE-C1

Paper Capacity : 3,500 sheets (80 gsm)
Paper Type : Thin, Plain, Recycled, Color, Heavy, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab
Paper Size : A3, A4, A4R, A5R, B4, B5, B5R
Custom size : 139.7 x 182.0 mm to 330.2 to 487.7 mm
Paper Weight : 52 to 256 gsm
Power Source : 220-240V, 50/60Hz, 1.2A
Dimensions (WxDxH) : 633 x 686 x 574 mm
(attached to the main unit)
Weight : Approx. 68 kg

Hardware Accessories

Card Readers

COPY CARD READER-F1
COPY CARD READER ATTACHMENT-A4

Others

UPRIGHT CONTROL PANEL-J1
UTILITY TRAY-B1
TAB FEEDING ATTACHMENT KIT-B1
SHIFT TRAY-F1
NUMERIC KEYPAD-A1
FINISHER JOGGER KIT-A1

Security Options

Device Security

iR-ADV SECURITY KIT-AJ1 FOR IEEE 2600 COMMON CRITERIA CERTIFICATION
(available at a later schedule)

Data Security

250GB SSD-A1
1TB SSD-A1
MEMORY MIRRORING KIT-A1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1
PCL ASIAN FONT SET-A1
PCL PRINTER KIT-BD1/CK1
PS PRINTER KIT-BD1/CK1

Barcode Printing

BARCODE PRINTING KIT -D1

System Accessories

SERIAL INTERFACE KIT-K3
NFC KIT-E1
COPY CONTROL INTERFACE KIT-A1
CONNECTION KIT-A2 FOR BLUETOOTH LE

Fax Accessories

SUPER G3 FAX BOARD-AX1
SUPER G3 2ND LINE FAX BOARD-AX1
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1

Consumables

STAPLE-N1
STAPLE P1
STAPLE-CARTRIDGE-X1
STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification table on your local Canon web site.

MAIN CONFIGURATION OPTIONS

MFP MODEL



BASIC OUTPUT OPTION



- COPY TRAY-R2**
- Capacity 250/100 sheets
 - (1-sided/2 sided 80gsm)



- PAPER DECK UNIT-E1**
- 3,500-sheet capacity
 - Supports A4/B5



- POD DECK LITE-C1**
- 3,500-sheet capacity
 - 52 to 256 gsm
 - Supports up to SRA3
 - User adjustable

FINISHER SPECIFICATION



- BOOKLET FINISHER - AC 1 (External)**
(IR-ADV 8986 only)
- 3-trays, 3,500 - sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 65 sheets (90gsm) 20 x 10 sets (52-105gsm)
 - Booklet-making up to 20 sheets
 - Dimensions (W x D x H): 656 mm x 623 mm x 1,195 mm
 - Weight: Approx. 60 kg
 - Supports Eco Stapling and Staple On Demand
 - Supports optional 2/4 and 2/3 Hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 2/3 Hole Puncher Unit-A1



- STAPLE FINISHER - AC 1 (External)**
(IR-ADV 8986 only)
- 3-tray, 3,500 - sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 65 sheets (90gsm)
 - Dimensions (W x D x H): 656 mm x 623 mm x 1,195 mm
 - Weight: Approx. 36 kg
 - Supports Eco Stapling and Staple On Demand
 - Supports optional 2/4 and 2/3 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 2/3 Hole Puncher-A1




- MULTI FUNCTION PROFESSIONAL PUNCHER- C1**
- Supports various die sets
 - Up to 300 gsm
 - Supports SRA3, A3, A4, A4R
 - Dimensions (W x D x H): 445 mm x 795 mm x 1,040 mm




- BOOKLET FINISHER-X1 (External)**
- 3-tray, 4,250-sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 100 sheets (80gsm) 20 sheets x 5 sets (60-80gsm)
 - Booklet-making up to 20 sheets and saddle-folding up to 5 sheets
 - Power Source: 100-240V AC, 50-60 Hz, 2.8A
 - Dimensions (W x D x H): 896 mm x 765 mm x 1,040 mm
 - Weight: Approx. 110 kg
 - Supports optional internal 2/4, S4 and 2/3 Holes 4-hole puncher (Puncher Unit-BF1 & BG1) and booklet trimming (Inner Booklet Trimmer-A1)



- STAPLE FINISHER-X1 (External)**
- 3-tray, 4,250-sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 100 sheets (80gsm)
 - Power Source: 100-240V AC, 50-60 Hz, 2.8A
 - Dimensions (W x D x H): 782 mm x 765 mm x 1,040 mm
 - Weight: Approx. 64 kg
 - Supports optional internal 2/3 and 2/F4-hole puncher (Puncher Unit-BF1 and BG1)



- DOCUMENT INSERTION UNIT- R1**
- Insert preprinted sheets
 - Up to SRA3, A3, A4, A4R, B4, B5, B5R
 - Custom size 182 x 182mm to 330.2 x 487.7mm
 - 2 trays
 - 400-sheet total capacity
 - Dimension (W x D x H) 336 x 793 x 1,407 mm



- PAPER FOLDING UNIT- K1**
- Z-fold, C-fold, Half-fold, Accordion Z-fold (52-105 gsm)
 - Double-parallel fold (52-105 gsm)

BOOKLET TRIMMER- G1
*Require Booklet Finisher-AG



- BOOKLET FINISHER-AG (External)**
- 2-tray, 5,000-sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 100 sheets (80gsm)
 - Booklet-making up to 25 sheets X10 sets (52-80gsm) and saddle-folding up to 5 sheets
 - Power Source 220-240V, 50-60 Hz, 8A
 - Dimensions (W x D x H): 1060mm x 792mm x 1,239mm
 - Weight: Approx. 182 kg
 - Supports optional internal 2/4 and 2/3-hole puncher (Puncher Unit-BT1, BU1 and BS1) and optional booklet trimming (Booklet Trimmer-D1)
 - Precise output stacking alignment
 - Enhanced durability for high volumes



- STAPLE FINISHER-AG (External)**
- 2-tray, 5,000-sheet capacity
 - Paper Weight: 52 - 256gsm
 - Corner and double stapling up to 100 sheets
 - Power Source: 220-240V, 50-60 Hz, 8A
 - Dimensions (W x D x H): 890 mm x 792 mm x 1,239 mm
 - Weight: Approx. 130 kg
 - Supports optional internal 2/F4 and S4 Holes and 2/3 hole puncher (Puncher Unit-BU1 and BS1)
 - Precise output stacking alignment
 - Enhanced durability for high volumes



To arrange for a demonstration, simply contact any of our offices below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte.Ltd. | 1 Fusionopolis Place #15-01 Galaxis Singapore 138522
Tel: 65-67 99 8888 | Fax: 65-6799-8882 | www.canon-asia.com | www.canon.com.sg

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximate. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners.

uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte Ltd.

0230W193© 2023 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.